

BEGA**45 488.1 P**

Pendant luminaire for indoor use

Project · Reference number

Date

Product data sheet

Application

Pendant luminaire · indoor luminaire for free-radiating and uniform light with white synthetic globe and with metal housing.

Product description

Metal housing and canopy

Colour white

White synthetic sphere

White flex suspension $3 \times 0,75 \square$

with 1 steel messenger wire

Overall length of luminaire approx. 2000 mm

Connecting terminals $2.5 \square$

Earth conductor connection

Lampholder E 27

Safety class I

Impact strength IK10

Protection against mechanical

impacts < 20 joule

CE – Conformity mark

Weight: 2.9 kg

Lighting technology

Luminaire data for the DIALux lighting design program for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at www.bega.com.

Lamp

Luminaire with lampholder E 27

Lamp output max. $1 \times 150 \text{ W}$

45 488.1 P K2

inclusive BEGA LED lamp **13565**

dimnable

LED 12 W

1400 lm

Colour temperature

2700 K

45 488.1 P K3

inclusive BEGA LED lamp **13592**

dimnable

LED 12 W

1400 lm

Colour temperature

3000 K

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

Article No. 45 488.1 P

Colour temperature of the supplied LED lamp

optionally 2700 K or 3000 K

2700 K – article number + **K2**

3000 K – article number + **K3**

Optional finishes

- White
- Stainless steel
- Chrome
- Brass

code number **.1**

code number **.2**

code number **.3**

code number **.4**

